

CHAINWAY®



R2

UHF RFID Bluetooth Reader



Bluetooth



1D Barcode



2D Barcode



UHF

Chainway R2 is a newly-developed handheld data collection device with stylish design and incredible performance. It delivers superior UHF reading and writing, barcode scanning, transmits data to the data center via Bluetooth with ease. It can complete tasks in inventory management, asset management, and inspection etc.

Specification

Physical Characteristics

Dimensions	282 x 117.5 x 32 mm / 11.10 x 4.63 x 1.26 in.
Weight	334 g / 11.78 oz. (with battery)
Colour	White
Appearance material	Plastic
Keypad	PWR button (side), up, down, return, ok, SCAN button (front)
Power	Battery specification: 5200mAh removable battery
	Standby: over 70 hours (keeping bluetooth connected)
	Continuous use: up to 6 hours (UHF reading)
	Charging time: 3-4 hours (with standard adaptor and USB cable)
Display	1.77 inch, 128 x 160
Indicator LED	Power, Work, Bluetooth
buzzer	Support
Interfaces	Micro-USB

Performance

MCU	Cortex-M3
	72MHz
Storage	50000 tags

User Environment

Operating Temp.	-4 °F to 122 °F / -20 °C to 50 °C
Storage Temp.	-40 °F to 158 °F / -40 °C to 70 °C
Humidity	5%RH - 95%RH non condensing
Drop Specification	Multiple 1.5 m / 4.9 ft. drops to concrete across the operating temperature range
Tumble Specification	1000 x 0.5 m / 1.64 ft. falls at room temperature
ESD	±15 KV air discharge, ±8 KV conductive discharge

Developing Environment

SDK	Android / IOS
Tool	Android Studio / Xcode
Language	Java / Objective-C

Communication

Bluetooth	Bluetooth 4.0, BLE
------------------	--------------------

Data Collection

Barcode Scanning (Optional)

2D Imager Scanner	SE2707
1D Symbologies	UPC/EAN, Code128, Code39, Code93, Code11, Interleaved 2 of 5, Discrete 2 of 5, Chinese 2 of 5, Codabar, MSI, RSS, etc.
2D Symbologies	PDF417, MicroPDF417, Composite, RSS, TLC-39, Datamatrix, QR code, Micro QR code, Aztec, MaxiCode; Postal Codes: US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal, Dutch Postal (KIX), etc.

UHF

Engine	CM710-1 module based on Impinj E710 CM2000-1 module based on Impinj Indy R2000
Antenna	Linear Polarized antenna (4dBi)
Frequency	920-925MHz/902-928MHz/865-868MHz
Protocol	EPC C1 GEN2 / ISO18000-6C
Module power	1W (30dBm, support +5~+30dBm adjustable)
	2W Optional (33dBm, for Latin America, etc.)
R/W range	Up to 15m(open outdoors, Impinj MR6 tag)
Fastest Read Rate	900+ tags/sec

* Ranges and rates depend on tags and environment

Accessories (See details in Accessory Guide)



AC Adapter



USB cable

Notice: Product specifications are subject to change without prior notice. / Model: R2 / Update Date: 2021-10-15

CHAINWAY®

Shenzhen Chainway Information Technology Co., Ltd

Address: 9F, Building2, Phase 2, Gaoxinqi Industrial Park, Liuxian 1st Rd., Bao'an District, Shenzhen, Guangdong 518102, China

Tel: 0086-755-23223316

Fax: 0086-755-23223310

Email: sales@chainway.cn

Web: <http://www.chainway.net>