













C70

Thermometry Mobile Data Terminal

- 
Android
- 
4G
- 
WiFi
- 
Bluetooth
- 
1D Barcode
- 
2D Barcode
- 
IRIS
- 
NFC
- 
Camera
- 
GPS

Chainway C70 is a high-performance intelligent handheld terminal which designed for temperature measurement. It is developed based on Android system, with high-performance processor, first-class configuration and fast operation, this device can be widely used in multiple temperature measurement scenarios. Temperature measurement module on top is more convenient for the user to operate, and helps the user to quickly realize information management and improve work efficiency.



Specification

Performance

CPU	Cortex-A53 2.5 / 2.3 GHz Octa-core
RAM+ROM	3GB+32GB / 4GB+64GB
Expansion	Supports up to 128 GB Micro SD card
Operating System	Android 8.1; SafeUEM supported Android 11; SafeUEM supported. Committed support for a future upgrade to Android 12, 13, and Android 14 pending feasibility

Communication

Android 8.1

WLAN	IEEE802.11 a/b/g/n/ac, 2.4G/5G dual-band, internal antenna 2G: 900/1800 MHz 3G: WCDMA: B1,B8 CDMA2000 EVDO: BC0 TD-SCDMA: B34,B39
WWAN (China)	4G: B1,B3,B5,B8,B34,B38,B39,B40,B41 CDMA2000 EVDO: BC0 TD-SCDMA: B34,B39
WWAN (Europe)	2G: 850/900/1800/1900 MHz 3G: B1,B2,B4,B5,B8 4G: B1,B3,B5,B7,B8,B20,B40
WWAN(America)	2G: 850/900/1800/1900 MHz 3G: B1,B2,B4,B5,B8 4G: B2,B4,B7,B12,B17,B25,B66
WWAN (Others)	Depending on the country's ISP
Bluetooth	Bluetooth v2.1+EDR,3.0+HS,v4.1+HS
GNSS	GPS/AGPS, GLONASS, BeiDou; internal antenna

Android 11

WLAN	IEEE802.11 a/b/g/n/ac, 2.4G/5G dual-band, internal antenna 2G: GSM850/GSM900/DCS1800/PCS1900 3G: WCDMA: B1/B2/B4/B5/B8 CDMA2000 EVDO: BC0 TD-SCDMA: A/F
WWAN	4G: B1/B2/B3/B4/B5/B7/B8/B12/B17/B20/B28A/B28B/B34/B38/B39/B40/B41 CDMA2000 EVDO: BC0 TD-SCDMA: A/F
Bluetooth	Bluetooth 5.0
GNSS	GPS/AGPS, GLONASS, BeiDou; internal antenna

Physical Characteristics

Dimensions	163.8 x 79.2 x 13.8 mm / 6.45 x 3.12 x 0.54 in.
Weight	242g / 8.5oz.
Display	5.2" IPS LTPS 1920 x 1080
Touch Panel	Corning Gorilla Glass, multi-touch panel, gloves and wet hands supported
Expansion Slot	1 slot for Nano SIM card, 1 slot for Nano SIM or TF card
Interfaces	USB2.0 Type-C, OTG, supports TypeC headphones
Audio	Speaker, 2 microphones
Keypad	4 front keys, 1 power key, 2 scan keys, 1 multifunctional key
Power	Main battery: Li-ion, rechargeable, 4000mAh Standby: over 300 hours Continuous use: over 12 hours (depending on user environment) Charging time: 2-3 hours (with standard adaptor and USB cable)
Sensors	Light sensor, proximity sensor, gravity sensor

Developing Environment

SDK	Software Development Kit
Language	Java
Tool	Eclipse / Android Studio

User Environment

Operating Temp.	-4°F to 122°F / -20°C to 50°C
Storage Temp.	-40°F to 158°F / -40°C to 70°C
Humidity	5%RH - 95%RH non condensing
Drop Specification	Multiple 1.8m / 5.9ft drops (at least 20 times) to the concrete across the operating temperature range
Tumble Specification	1000 x 0.5m/1.6ft falls at room temperature
Sealing	IP65 / IP67 per IEC sealing specifications
ESD	±15KV air discharge, ±6KV conductive discharge

Data Collection

Temperature Collection

Measure Position	Human forehead / Object surface
Measure Method	Non-contact / Infrared
Measure Distance	1 - 3 cm
Measure Range	Human forehead: 32°C to 42.9°C; Object surface: -40°C to 115°C;
Measure Accuracy	Human forehead: ±0.2°C; Object surface: ±0.5°C;
Measure Duration	1 sec
Spectral Range	5.5 -15 μm
Resolution	0.02°C

*The infrared module has 80 degrees limitation, the best measure angle should be in this range.

Camera

Rear Camera	13MP Autofocus with flash
Front Camera (optional)	5MP camera

NFC

Frequency	13.56MHz
Protocol	ISO14443A/B, ISO15693, NFC-IP1, NFC-IP2, etc.
Chips	M1 card (S50, S70), CPU card, NFC tags, etc.
Range	2-4cm

Barcode Scanning (Optional)

2D Imager Scanner	Zebra SE4710 / Honeywell N6603
1D Symbolologies	UPC/EAN, Code128, Code39, Code93, Code11, Codabar, Interleaved 2 of 5, Discrete 2 of 5, Chinese 2 of 5, MSI, RSS, etc.
2D Symbolologies	PDF417, MicroPDF417, Composite, RSS, TLC-39, Datamatrix, QR code, Micro QR code, Aztec, MaxiCode; Postal Codes: US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal, Dutch Postal (KIX), etc.

Iris (optional)

Rate	< 150 ms
Range	20-40 cm
FAR	1/10000000
Protocol	ISO/IEC 19794-6, GB/T 20979-2007

*Iris is alternative to front camera.

Accessories(See details in Accessory Guide)



AC Adaptor



USB Cable



Sim Tray Ejector



Lanyard



Cradle (Optional)



Holster(Optional)

Notice: Product specifications are subject to change without prior notice. / Model: C70 / Update Date: 2022-01-14

CHAINWAY®

Shenzhen Chainway Information Technology Co., Ltd

Address: 9F, Building2, Phase 2, Gaoxinqi Industrial Park, Liuxian 1st Rd., Bao'an District, Shenzhen, Guangdong 518102, China

Tel: 0086-755-23223316

Fax: 0086-755-23223310

Email: sales@chainway.cn

Web: http://www.chainway.net